

# FMC800

PLUG AND PLAY TRACKER WITH  
4G LTE CAT 1 CONNECTIVITY



4G

FUTURE-PROOF  
NETWORK SUPPORT



FAST & EASY  
INSTALLATION



RELIABLE CONNECTION  
BETWEEN DEVICES

## 4G CAT 1

Reliable 4G (LTE Cat 1) connection  
with fallback 2G (GSM) network

## OBDII PORT CONNECTION

Allows installing tracker in a few  
seconds

## BLUETOOTH 4.0

Bluetooth for external devices and  
Low Energy sensors

## CRASH DETECTION

Crash detection functionality working  
according accelerometer data



LIGHT  
VEHICLES



MOTORBIKES



INSURANCE  
TELEMATICS



COURIER  
DELIVERY  
SERVICES



RENTAL AND  
LEASING

FMx8 series devices are EASY to use and FAST to install. The number "8" brings everything together in one place and stands out with its simplicity of basic tracking.

Teltonika FMC800 tracker is a small OBDII Plug and Play device with 4G LTE Cat 1 and Bluetooth connectivity. An extremely fast and easy installation allows connecting device in a few seconds! No tools or engineers are required for installation.

Thanks to that, FMC800 tracker perfectly suits for light vehicle tracking in applications like courier delivery service, car rental & leasing, insurance telematics and other industries, where simple integration is a must. It is a perfect solution for real time monitoring, specially for beginners and those, who are looking for new opportunities to expand their businesses.

FMC800 device has a built-in accelerometer, which provides accurate crash trace data. This tracker also supports various Bluetooth Low Energy sensors, beacons, firmware and configuration update via Bluetooth. All of that increase the number of possible use scenarios in any market. It is quick to install, easy to use and ready to start tracking in minutes!



**Module**

Name	FMC800-QJIB0: Quectel EG915U-EU with Teltonika TM2500
Technology	LTE CAT 1/GSM/GPRS/GNSS/BLUETOOTH

**GNSS**

GNSS	GPS, GLONASS, GALILEO, BEIDOU, QZSS, AGPS
Receiver	33 channel
Tracking sensitivity	-165 dBm
Position Accuracy	< 2.5 CEP
Velocity Accuracy	< 0.1 m/s
Hot start	< 1 s
Warm start	< 25 s
Cold start	< 35 s

**Cellular**

2G bands	FMC800-QJIB0: GSM: B2/B3/B5/B8
4G bands	FMC800-QJIB0: LTE FDD: B1/B3/B7/B8/B20/B28
Data transfer	LTE: LTE FDD: Max 10Mbps (DL)/Max 5Mbps (UL) GSM: GPRS: Max 85.6Kbps (DL)/Max 85.6Kbps (UL)
Data support	SMS (text/data)

**Power**

Input voltage range	10 - 30 V DC with overvoltage protection
Internal Back-up battery	170 mAh Li-Ion battery 3.7 V (0.63 Wh)
Internal fuse	3 A, 125 V

**Bluetooth**

Specification	4.0 + LE
Supported peripherals	Temperature and Humidity sensor, Inateck Barcode Scanner, Universal BLE sensors support

**Physical specification**

Dimensions	67,2 x 49,6 x 25 mm (L x W x H)
Weight	63 g

**Operating environment**

Operating temperature (without battery)	-40 °C to +85°C
Storage temperature (without battery)	-40 °C to +85 °C
Operating humidity	5% to 95% non-condensing
Ingress Protection Rating	IP41
Battery charge temperature	0 °C to +45 °C
Battery discharge temperature	-20 °C to +60 °C
Battery storage temperature	-20 °C to +45 °C for 1 month -20 °C to +35 °C for 6 months

**Interface**

Connection	OBDII socket
GNSS antenna	Internal High Gain
GSM antenna	Internal High Gain
USB	2.0 Micro-USB
LED indication	2 status LED lights
SIM	Micro-SIM
Memory	128MB internal flash memory

**Features**

Sensors	Accelerometer
Scenarios	Green Driving, Over Speeding detection, Jamming detection, GNSS Fuel Counter, Excessive Idling detection, Unplug detection, Towing detection, Crash detection, Auto Geofence, Manual Geofence, Trip
Sleep modes	GPS Sleep, Online Deep Sleep, Deep Sleep, Ultra Deep Sleep
Configuration and firmware update	FOTA Web, FOTA, Teltonika Configurator (USB, Bluetooth), FMBT mobile application (Configuration)
SMS	Configuration, Events, Debug
GPRS commands	Configuration, Debug
Time Synchronization	GNSS, NITZ, NTP
Ignition detection	Accelerometer, External Power Voltage

**Certification & Approvals \***

Regulatory	FMC800-QJIB0: CE RED, E-Mark, RCM
------------	-----------------------------------

\* in progress